

AutoPi TMU CAN-FD

Faster data rate at your fingertips



Bluetooth



**Raspberry Pi 3
Model A+ and**



Up



GPIO Pins



HDMI Port



USB Port



Voice Speaker



**Accelerometer/
Gyroscope**



**2x Dedicated
CAN-FD**



GPS/GLONASS



**4G/3G LTE
Cat 4 Modem**



WiFi



**Native Real-time
Clock**



Key Benefits

4G/LTE with global coverage

The integrated modem with worldwide coverage.

Built in 2x CAN-FD interface

Increased automotive bandwidth and speed with dual CAN-FD.

Factory integrated unit or aftermarket add-on

Use as a factory integrated OEM device or aftermarket add-on.

Integrated power-safe functionality

Proven and experienced power fail-safe functionality integrated.

Runs full Linux OS

Boost a well proved and tested OS, with guarantee for stability.

Can be extended to almost any usage


Allows extension to both business and personal use cases.

Upgradeable CPU/RAM

Upgrade the device to Raspberry Pi 3B+ or Raspberry Pi 4.

Automotive certified (CE/FCC)

Certified to automotive standards for global usage.



Upgraded automotive interface

The device comes with a 2x CAN FD interface and can be further expanded with additional CAN interfaces. Support for Diagnostics over IP (DoIP) using Raspberry Pi 3B+ and up




Runs LINUX OS

AutoPi Core is based on a full LINUX OS (Raspberry Pi OS), with endless possibilities for extitons and integrations. Well proven and tested OS, with high endurance.



Open source-software

The device runs on an open source-software, which allows users to build a custom code on top of that. All drivers and implementations in AutoPi Core is available from our GitHub repository.



Computing Power

Quad Core CPU provides incredible speed and functionality. Broadcom BCM2837B0 64-bit Quad-core CPU at 1.4 GHz. 512MB RAM and also an integrated GPU. Upgradeable to even more speed with Raspberry Pi 4.



Standard

Suited for all Raspberry Pi editions



1x ext. ant., 2x USB-A

Suited for Raspberry Pi 3B+ and up



2x ext. antenna

Suited for Raspberry Pi 3B+ and up



1x ethernet, 2x USB-A

Suited for Raspberry Pi 3B+ and up



3x external antenna

Suited for Raspberry Pi 3A+

Technical Specifications

Processor	Broadcom BCM2837B0, Cortex-A53 (ARMv8), 64-bit quad-core SoC @ 1.4 GHz (built-in Raspberry Pi 3 model A+) Upgrade (RPI3 B+): Broadcom BCM2837B0 quad-core A53 (ARMv8) 64-bit @ 1.4GHz Upgrade (RPI4 B): Broadcom BCM2711, Quad core Cortex-A72 (ARM v8) 64-bit SoC @ 1.5GHz
Memory	512MB LPDDR2 SDRAM (built-in Raspberry Pi 3 model A+) Upgrade (RPI3 B+): 1GB LPDDR2 SDRAM Upgrade (RPI4 B): 2GB, 4GB or 8GB LPDDR4-3200 SDRAM (depending on model)
Storage	32GB Micro SD Card High Endurance Class 10 UHS-1 (Raspbian Jessie OS and AutoPi Core software installed) (Upgradeable to 128GB)
Size, Weight and Casing (NEW)	Size and weight: TBD Casing: Improved expansion options with exchangeable back shield for external antennas, additional USB ports, ethernet port.
Modem	Integrated 4G/LTE Cat 4 connection (3G/EDGE fallback) 150Mbit DL / 50Mbit UL Worldwide support in a single device 4G LTE Bands (Global): B1 / B2 / B3 / B4 / B5 / B7 / B8 / B12 / B13 / B18 / B19 / B20 / B25 / B26 / B28 / B38 / B39 / B40 / B41 3G Fallback (WCDMA): B1 / B2 / B4 / B5 / B6 / B8 / B19 EDGE Fallback: B2 / B3 / B5 / B8 / Quad-band
Certifications	EN 301 489-1 v2.2.0 EN55025:2008 EN 50498 and Directive 2004/104/EC ISO 7637-2:2011 EN 301 489-3 V2.1.1 FCC 47 CFR Part 15, Class A:10-1-17 Edition
GPS	Integrated GPS + A-GPS. Supports: GPS/GLONASS/BeiDou/Galileo/QZSS
Power	Line Voltage: 12.5V AC (Car battery power). Up to 35V (Trucks). Support for trucks with up to 35V Built-in Power Management system to prevent the vehicle's battery from being drained
Expansion	1 X USB: Highspeed Micro USB 2.0 (Additional when using Raspberry Pi 3B+ and up) GPIO: UART/I2C/SPI
Wireless	Built on Cypress CYW43455 Chipset WiFi: 2.4GHz and 5GHz IEEE 802.11.b/g/n/ac wireless LAN Bluetooth: Bluetooth 4.2 + Bluetooth Low Energy (BLE)
Accelerometer	Built in 3-axis accelerometer
Gyroscope (NEW)	Built in 3-axis gyroscope
Automotive Interface (NEW)	2 X CAN-FD: CAN-FD interface with up to 5Mbps Data rate with integrated CAN data filter DoIP: Built in support for DoIP using RPI3 B+ and up
Input slots	SD Card: Included (See storage) SIM Card: Nano SIM – <i>Not Included</i>
Audio	Built-in speakers Mini Jack out (audio)
Video Out	HDMI @ 1080P60 Video Output
Absolute Maximum Operating Environment	Operating Temperature: -20° TO 70° C (-4° TO 158° F) Relative Humidity: 0% TO 75% Noncondensing
Operating System	Raspbian OS with preconfigured AutoPi Core
Processor	Broadcom BCM2837B0, Cortex-A53 (ARMv8), 64-bit quad-core SoC @ 1.4 GHz (built-in Raspberry Pi 3 model A+) Upgrade (RPI3 B+): Broadcom BCM2837B0 quad-core A53 (ARMv8) 64-bit @ 1.4GHz Upgrade (RPI4 B): Broadcom BCM2711, Quad core Cortex-A72 (ARM v8) 64-bit SoC @ 1.5GHz